


ERVITAL LIHCH FE 180 / PH 120

VDE 0812



ALEV GECİKTİRİCİ ÖZELLİK / DÜŞÜK DUMAN YOĞUNLUĞU / ZEHİRLİ VE KOROZİF GAZLARDAN ARINDIRILMIŞ DEVRE BÜTÜNLÜĞÜ MİNİMUM 180 DAKİKA / MEKANİK ŞOKLU DEVRE BÜTÜNLÜĞÜ PH 120
FLAME RETARDANT CHARACTERISTIC / LOW SMOKE EMISSION / WITHOUT POISONED AND CORROSIVE GASSES
CIRCUIT INTEGRITY 180 MINUTES (min) / CIRCUIT INTEGRITY WITH SHOCK PH 120



KULLANIM ALANLARI

İnsanların yoğun olarak bulunduğu kapalı ortamlarda Elektromanyetik karışım ve girişimlerin olduğu yerlerde

- Enstrüman ve kontrol mühendisliğinde
- Endüstriyel elektronikte
- Sinyal iletiminde
- Bina içi haberleşme sistemlerinde
- Güvenlik ve yangın ihbar sistemlerinde
- İnsan hayatının, değerli malzemelerin ve ekipmanların korunması gereken yerlerde

APPLICATION

- indoors where people are densely populated
- In places where there is electromagnetic interference
- Instrumentation and control engineering
- Industrial electronics
- For signal transmission
- Indoor communication systems
- In safety and fire alarm systems
- In places where human life and valuable materials and equipment need to be protected

KABLO YAPISI

1-İletken	IEC 60228; VDE 0295; EN 60228 SINIF 5 BÜKÜLÜ ELEKTROLİTİK TAVLI BAKIR
2-Yalıtkan	ÇAPRAZ BAĞLI SERAMİK FORMUNDA POLİMER KOMPAUND
3-Yalıtım Renk	DIN 47100
4-Büküm	UYGUN ADIMDA, KATLAR HALİNDE
5-Ayırıcı Bant	PES BANT + CAM ELYAF BANT
6-Ekran	KALAYLI BAKIR ÖRGÜ
7-Kılıf	EN 50290-2-27 HFFR KOMPAUND
8-Kılıf Rengi	RAL 2003 TURUNCU

CONSTRUCTION

1-Conductor	IEC 60228; DIN VDE 0295; HD383 CLASS 5 STRANDED ELECTROLYTIC BARE COPPER
2-Insulation	CROSS-LINKED CERAMIC FORMING POLYMER COMPOUND
3-Colour Code	DIN 47100
4-Stranding	IN LAYERS OF OPTIMUM PITCH
5-Wrapping	PES TAPE + GLASS FIBRE TAPE
6-Screen	TINNED COPPER BRAID
7-Sheath	EN 50290-2-27 HFFR COMPOUND
8-Sheath Colour	RAL 2003 ORANGE

TEKNİK ÖZELLİKLER TECHNICAL CHARACTERISTICS

İLETKEN DİRENCİ CONDUCTOR RESISTANCE		YALITIM DİRENCİ (min) INSULATION RESISTANCE (min)	EFEKTİF KAPASİTE MUTUAL CAPACITANCE	AKIM TAŞIMA KAPASİTESİ CURRENT CARRYING CAPACITY	
mm ²	Ω/km	MΩxkm	120 nF/km	mm ²	A
0,22	79	0,22 ve 0,34 mm ² = 200		0,22	2,5
0,34	56	>0,50 mm ² = 20		0,34	4,5
0,50	39			0,50	6,0
0,75	26			0,75	13
1,0	19,5			1,0	16
1,5	13,3			1,5	20
2,5	7,98			2,5	25

BÜKÜLME YARIÇAPI BENDING RADIUS	TEST VOLTAJII (50 Hz 1 Dk) DMR/DMR TEST VOLTAGE (50 Hz 1 Min) CORE/CORE	ÇALIŞMA VOLTAJII OPERATING VOLTAGE	ÇALIŞMA SICAKLIĞI TEMPERATURE RANGE
7,5X D	0,22 ve 0,34 mm ² = 1200 V >0,50 mm ² = 2000 V	0,22 ve 0,34 mm ² = 250 V >0,50 mm ² = 300/500 V	- 40°C - +70°C

YANGIN PERFORMANS TESTLERİ FLAME PERFORMANCE TESTS

ALEV GECİKTİRİCİLİK TESTİ FLAME RETARDANT TEST	ALEV YAYILIMI TESTİ FLAME PROPAGATION TEST	DUMAN YOĞUNLUĞU TESTİ SMOKE DENSITY TEST	KOROZİF GAZ TESTİ TEST ON CORROSIVENESS COMBUSTION GASES
IEC 60332-1-2 VDE 0482-332-1-2 EN 60332-1-2 BS EN 60332-1-2	IEC 60332-3-24 VDE 0482-332-3-24 EN 60332-3-24 BS EN 60332-3-24	IEC 61034-2 VDE 0482-1034-2 EN 61034-2 BS EN 61034-2	IEC 60754-2 VDE 0482-267-2-3 EN 50267-2-3 BS EN 50267-2-3
HALOJENSİZLİK TESTİ HALOGEN FREE TEST	DEVRE BÜTÜNLÜĞÜ TESTİ (FE 180) CIRCUIT INTEGRITY TEST (FE 180)	MEKANİK ŞOKLU DEVRE BÜTÜNLÜĞÜ TESTİ (PH 120) CIRCUIT INTEGRITY WITH SHOCK TEST (PH 120)	
IEC 60754-1 VDE 0482-267-2-1 EN 50267-2-1 BS EN 50267-2-1	IEC 60331-23	EN 50200 VDE 0482-200 BS EN 50200	

NOTLAR NOTES

* Bu kablo PH 180 testlerinde VDE tarafından onaylanmış ve sertifikalandırılmıştır.

* This cable has been approved and certified by VDE on PH 180 tests